



OUR CLIENTS



ORASCOM
CONSTRUCTION



شركة الخدمات التجارية البترولية
إحدى شركات قطاع البترول



ELSEWEDY
ELECTRIC

DSV



ADVANSYS
PROJECTS

Ecologi

ABOUT US

PHOENIX is a premier manufacturer of firefighting apparatus, serving all sectors. We are committed to excellence, emphasizing dedication, a helping mentality, and deep expertise. Our standout aftercare services and exceptional communication ensure our clients receive unparalleled support and reliable solutions. At PHOENIX, we protect lives and properties with top-quality equipment and innovative, customized solutions.


PRODUCT CATALOGUE




MAVERICK



OUR PRODUCTS




1 Fluorine Free Foam



- Non-toxic foam concentrate
- Free from fluorochemicals and fluoropolymers
- Can be used with both fresh and salt water biodegradable

2 AFFF 1, AFFF 3, AFFF 6



- Effective extinguishment of Class A and B
- Inherent self-sealing property
- Highly advantageous for rapid rescue operations

3 AR-AFFF



- Specially formulated non-toxic
- Viscous foam liquid concentrate
- For use in hydrocarbon as well as polar solvent fires

4 Protein Foams



- Containing hydrolysed protein concentrate
- Superior burn-back resistant character over hydrocarbon fuel fire
- Superior foam blanket which prevents the fuel from re-ignition
- It contains natural protein and no harmful synthetic detergents

1 CO2 Extinguishing System



- UL Listed
- Very versatile and effective on a wide range of flammable and combustible materials.
- No residue- nothing to clean
- %0 Ozone Depletion Potential (ODP)
- Low cost of system and maintenance

2 1-12-FK 5 Extinguishing System



- UL Listed / VDS Approved
- Cylinder Capacity Ranges from 30Li up to 180Li.
- high filling ratio that can be up to 1,2kg/L
- 25 Bar and 50 Bar Options

3 Triple Star For Kitchen Systems



- LPCB Certified
- Easy / Flexible installation
- Quick & Effective suppression
- Highly Dependable: no electricity or moving parts
- 16,9 or 25 liters

1 Bladder Tank



- Capacity: up to 10,000 Gallon
- Horizontal and Vertical Installation
- Foam Proportioners: 50NB up to 200NB
- Wide Flow Range: 75 LPM to 30,000 LPM
- MOC: Carbon Steel and Stainless Steel
- Working Pressure: 12 Bar

2 Foam Chamber



- Size: 50NB, 65NB, 80NB & 100NB
- Flow Range 66 LPM to 2,838 LPM
- Carbon Steel & Stainless Steel

3 Foam Maker



- Wide Flow Range Capacity : 66 to 1476 LPM
- Effective for operation at low inlet pressure ranging 2.1 Bar to 7 Bar
- Compact Sizes : 50 NB, 65 NB & 80 NB
- UL Listed for MOCs : Carbon Steel, Stainless Steel 304/L & 316/L
- Listed with AFFF %3 & AR-AFFF 3 x %3 Foam Concentrates